

# DuoCartSwitch DCS1 for EFOY Pro Series

## Longer autonomy for your applications



**NEW**

The DuoCartSwitch: One EFOY Pro, two EFOY fuel cartridges.

- ✓ Doubled autonomy
- ✓ Complete draining of the EFOY fuel cartridge.
- ✓ Methanol consumption can be measured
- ✓ Automatic switch from the operating cartridge to the reserve cartridge



# DuoCartSwitch DCS1

## Increased autonomy

Thanks to the connection of two fuel cartridges, service intervals and costs can be reduced.

## Completely emptied fuel cartridges

By using a reserve cartridge, the first one can always be completely emptied without risking an interruption of the system.

## Automatic switch

The DuoCartSwitch switches automatically from the operating fuel cartridge to the reserve fuel cartridge. If a Modem is used, the information will be sent to the customer.

## Measures the methanol consumption

The consumed methanol of the operation fuel cartridge is measured. This information is available via the Hyper Terminal programme and the modem. The counter is reset by every fuel cartridge switch.

### Standard equipment

DuoCartSwitch DCS1, Port Doppler, Dataline Cat5

### DuoCartSwitch - Specifications

Dimensions	174 x 119 x 96 mm
Weight	0,7 kg
Operating temperature	-20 to +45°C
Compatible fuel cells	EFOY Pro 600, 1200, 1600, 2200
Compatible fuel cartridges	M5, M10, M28 (with M28 adapter)
Nominal voltage	12 V / 24 V
Firmware	Version 9.17 and higher (prod. Date sept. 2009)
Switchsignal	GPO (General Purpose Output) at PIN 1 of EFOY Pro

091009\_DuoCartSwitch\_vers.2